

T180

Thermal Ink Jet Printer

ARYAKGK

TIJ Printer

- پشتیبانی از موس و کیبرد بیسیم
- هد مستقل جهت نصب در هر زاویه
- قابلیت چاپ کد دیتا ماتریس GS1
- صفحه نمایش لمسی با منو فارسی
- سرعت چاپ 460 M/Min



- سخت افزار صنعتی و حرفه ای
- دارای چیپ ست صنعتی آمریکایی AM3358
- دارای گرید صنعتی Xilinx Spant6 FPGA
- برد کنترلر هد با چیپست اختصاصی TIJ ASIC
- پشتیبانی از جوهر های اصل و تحت لیسانس HP
- نرم افزار قدرتمند و هوشمند
- سیستم عامل لینوکس
- رابط کاربری ساده و آسان
- چاپ اطلاعات کد رندم و رد یابی کالا
- محاسبه میزان مصرف جوهر برحسب پیام و تعداد چاپ



T180

Thermal Ink Jet Printer

ARYAKGK

TIJ Printer

Technical Parameters

Machine	Operating System	Embedded Operating System
	Main Hardware	American TI AM3358 industrial grade CPU/USA Xilinx Spant6 industrial grade FPGA / TIJ dedicated ASIC chip
	Communication Interface	Network Interface USB/RJ45 to RS-232
	External Interface	Photocell, Encoder, External Reverse/Inverse control, Alarm outputs, Serial Number external Reset, External data Selection.
	Supported Languages	Italian, English, French, Finnish, Arabic, Danish, German, Russian, Norwegian, Portuguese, Spanish, Japanese.
	Power Supply	100 - 240 Volts AC 50-60Hz input / 12.6Volts 3Amps DC output
	Body Material	ABS metal (stainless steel)
	Dimension	230mm x 137mm x 97mm
Printing Head	Working Environment	Max Temp 55C Degrees / Humidity 30% to 70% RH
	Nozzle Type	Thermally Foamable Head TIJ2.5
	Print Accuracy	150DPI / 300DPI / 600DPI
	Print Height	Minimum 1mm / Maximum 12.7mm
	Printing distance	Optimum spray printing distance of 1-2 mm
	Print distance	1mm to 2mm
	Print Contents	Multi language Characters, 2DCode, Barcodes, Images, Serial Numbers, Date, Counters, Variable Database, RS232 to receive real data to print
	Printable Substrates	Cardboard, Plastic, Metal, Cables, Electronic components, Auto Parts, Industrial Chemical packaging, Pharmaceuticals and more.
	Ink Type	Aqueous or Solvent based 42ml Cartridges CISS
	Ink Color	Black, White, Red, Yellow, Blue, Green, Stealth, UV readable
	Cartridge Chip	Contactless RFID tags for automatic identification and recording ink parameters and consumptions

